

Low Volume Polishing Machine for R&D and Re-works.




Minimize Cost, Maximize

Performance

Application: Re-Work R&D Low Volume Production

SFP-70D

- High Performance
- Extremely Portable
- Battery Operable
- FC, SC, ST, MU, LC
- HPC or APC
- Low Insertion Loss
- Low Back Reflection
- up to 6 connectors





Honest Solutions in Fiber Optics.

www.sg-usa.com





Data Sheet

Key Features

- High performance Polishing for a variety of applications
- Ergonomic, simple design for ease-of-use.
- Extremely small sized, for high portability in the laboratory or in the field.
- Perfect for research or low volume re-works.
- · Short Cycle times (2 min. typical for re-works)
- Comes w/ hard shell carrying case for easy and safe transport

Standard Package

DescriptionPart #QtyMain BodySFP-70D21Operating ManualN/A1Cable HolderFP-CH1Allen Wrench SetFP-TS11 Amp FuseFP-F1A10AC/DC AdaptorAD201GreaseFP-GS1Transit CaseFP-CB071Shoulder StrapFP-SS1Rubber Pad 1PR07-5001Rubber Pad 2PR07-4801Glass PadPG07-4901Adhesive RemovalGA0720Rough PolishDR072Middle PolishDM07-BL2Final PolishSF0720			
Operating ManualN/A1Cable HolderFP-CH1Allen Wrench SetFP-TS11 Amp FuseFP-F1A10AC/DC AdaptorAD201GreaseFP-GS1Transit CaseFP-CB071Shoulder StrapFP-SS1Rubber Pad 1PR07-5001Rubber Pad 2PR07-4801Glass PadPG07-4901Adhesive RemovalGA0720Rough PolishDR072Middle PolishDM07-BL2	Description	<u>Part</u> #	<u>Qty</u>
Rough PolishDR072Middle PolishDM07-BL2	Main Body Operating Manual Cable Holder Allen Wrench Set 1 Amp Fuse AC/DC Adaptor Grease Transit Case Shoulder Strap Rubber Pad 1 Rubber Pad 2	SFP-70D2 N/A FP-CH FP-TS FP-F1A AD20 FP-GS FP-CB07 FP-SS PR07-500 PR07-480	1 1 1 10 1 1 1 1 1
Spacer for re-polish SP07-005 2	Rough Polish Middle Polish Final Polish	DR07 DM07-BL SF07	2 2 20

I.P.C. Polishing Fixtures

MU,LC Ferrule	PH07-FLM-6	
MU/PC	PH07-PM-6	
LC/PC	PH07-PL-6	
MU/APC	PH07-PU8A-6	
LC/APC	PH07-PL8A-6	
Also available for FC,SC, & ST		
I.P.C. = Independent Pressure Control		

Seikoh Giken USA., Inc. 5970 Unity Dr., Ste. D Norcross, GA 30071 USA 770-662-0708 tel. 770-662-0121 fax. sales@sg-usa.com



Specifications

Applicable Connectors: FC, SC, ST, LC, MU, D4, DIN, SMA905		
Weight:	3.2 kg	
Dimensions:	120mm W x 120mm D x 145mm H	
Power:	AC100-240V 50/60Hz, Optional Battery Avail.	
Polishing Time:	1.6 – 3.0 min.	
Motor Speed:	100rpm revolution 2.8rpm rotation	
Polishing Method:	rotation & revolution (Patent # 4979334)	
Plate Material:	Stainless Steel	
Plate size/ Film size:	70mm	

Available Fixtures, Pads, & Films

Description:	Holder Part #
SC,FC Ferrule	PH07-FF
FC/PC	PH07-FP
SC/PC	PH07-CP
ST/PC	PH07-SP
FC,SC APC Ferrule	PH07-FF8A
FC/APC	PH07-FP8A
SC/APC	PH07-CP8
More available, please contact	us for details
Description:	Film Part #
Adhesive Removal	GA07
Rough Polish	DR07
Middle Polish	DM07
Final Polish	HF07
Description:	Pad Part #
Rubber, 5mm, 80durometer	PR07-500
Glass, 4.9mm	PG07-490
Polishing Oil	PL-50



Honest Solutions in Fiber Optics.

www.sg-usa.com